

Contractor: _____ **Project:** _____

RTSH-P 54" - 96" W

Sizes		
Height	Width	Quantity



Non-penetrating and adjustable H-Stand support product consisting of strut channel framing and recycled rubber bases for safely supporting duct, cable tray, and/or pipe above the roof.

Compatible Base: [RTSSPB20HG]

Clearance: Adjustable height above +/-12".

Maximum Load Weight: Based on structural capacity of structure. See corresponding base submittal.

Hardware finish: [Electrogalvanized] or [Stainless Steel].

Load Bearing Cross Brace: 1-5/8" x 3-1/4" welded strut channel

Strut finish: [Pregalvanized (G90)], [Hot Dip Galvanized], or [Stainless Steel].

Spacing: Horizontal support spacing according to specification, or horizontal support spacing according to applicable building code. Do not exceed manufacturer's suggested spacing of 8-foot centers as loading permits.

Installation Instructions:

1. Install base on roof per base submittal.
2. Preload (1) 3/8" channel nut and bolt into one of the top two holes on the base receiver.
3. Insert upright components into bases with strut opening facing outward. Tighten bolt to 19 ft/lbs. to secure.
4. Preload (1) 3/8" channel nut and bolt into one of the top two *outside* holes in each of the cross brace receivers.
5. Slide the cross brace over the ends of the uprights. Be sure to orient the channel appropriately.
6. Level cross brace at the correct height and affix to the uprights by tightening the bolts to 19ft/lbs.
7. Install the snap pins through the uprights within 6" of the bottom of the cross brace receiver.
8. Install yellow caps on the tops of the uprights.

