

Contractor: \_\_\_\_\_ Project: \_\_\_\_\_

## RTSPUCES-24

Quantity: \_\_\_\_\_



Non-penetrating pipe support for roof mounted gas, conduit, solar, or other mechanical piping.

**Base Material:** Compression molded recycled rubber (97% recycled material).

**Base Dimensions:** 2X 12-inch Diameter. 143 in<sup>2</sup> surface contact.

**Pipe Clearance:** Adjustable height of 6 inches – 24 inches .

**Maximum Load Weight:** Based on structural capacity of structure:

286 lbs. at 2 PSI, 429 lbs. at 3 PSI (per support)

**Pipe Rests on** 22-1/2" x 1-5/8" x 1-5/8" 12-gauge strut channel.

**Threaded Rod/Hardware finish:** [Electrogalvanized] or [Stainless Steel].

**Strut finish:** [Electrogalvanized], [Hot Dip Galvanized], or [Stainless Steel].

**Spacing:** Horizontal support spacing according to pipe specification, or horizontal pipe support spacing according to applicable building code. Do not exceed manufacturer's suggested spacing of 8-foot centers as loading permits.

---

### Installation Instructions:

1. Place base on roof based on design layout.
2. Run pipe accordingly.
3. Connect pipe to base using pipe clamp or roller per application requirements.

\*\*\*\*NOTE: No adhesive is to be used with this product to attach to the roof.

