

Contractor: \_\_\_\_\_ Project: \_\_\_\_\_

## RTSSPB80HG

Direct Mount base for use in Heavy Duty H-Stands, Equipment supports, Crossover units, and Access Platforms.  
Compatible *only* with Sikla Framo 80 framing product.

**Base Material:** Solid Steel.

**Base Dimensions:** 8" Diameter x [18-1/2"] or [30-1/2"] .

**Clearance:** Minimum mount height of +/-20" above structure with 12" bar.

**Maximum Load Weight:** Based on structural capacity of roof substructure.

**Steel Component:** [12"] or [24"] 1-3/4" solid round bar welded to 1/4" steel plates.

**Steel finish:** [Hot Dip Galvanized].

**Hardware finish:** [Electrogalvanized] or [Stainless Steel].

**Spacing:** Horizontal support spacing according to pipe specification, or horizontal pipe support spacing according to applicable building code. Do not exceed manufacturer's suggested spacing of 8-foot centers as loading permits.

---

### Installation Instructions:

1. Place base on roof based on design layout.
2. Cut roofing membrane and insulation to expose structure.
3. Bolt base to structure using appropriate fastener.
4. Waterproof roofing penetration with flashing or a pitch-pocket.
5. Slide Framo 80 beam component of support onto fitting.
6. Secure with provided self forming screws. (4) ea.

