

## Rooftop Support Systems

a division of Eberl Iron Works, Inc.  
128 Sycamore Steet  
Buffalo, New York 14204

(888) 243-2669  
RTS@eberliron.com  
rooftopsupportsystems.com



# RTSEQ-R-4

## PRODUCT SUBMITTAL SHEET

### FOUR UNIT SUPPORT



### Description

Non-penetrating and adjustable condenser support consisting of strut channel framing and recycled rubber bases for safely supporting Mini-split units.

### Product Information

**Compatible Bases:** RTSPUCF11

**Clearance:** Adjustable height 12 in - 24 in

**Maximum Load Weight:** 800 lbs total. 200 lbs/unit

**Framing:** 1-5/8 in x 1-5/8 in, 12 gauge perforated strut channel

**Framing Finish:** Pre-Galvanized (ASTM 653), Hot Dip Galvanized (ASTM 123), or 304 Stainless Steel

**Hardware Finish:** Electro-Galvanized (ASTM B633) or 304 Stainless Steel

### Installation

1. Place base on roof based on design layout
2. Preload (1) 3/8 in channel nut and bolt into one of the top two holes on the base receiver
3. Insert upright components into bases with strut opening facing outward. Tighten bolt to 19 ft/lbs to secure
4. Preload (1) 3/8 in channel nut and bolt into one of the top two outside holes in each of the welded cross brace receivers
5. Slide the cross brace over the ends of the uprights. Be sure to orient the channel open side up
6. Level cross braces at the correct height and affix to the uprights by tightening the bolts to 19ft/lbs
7. Attach the remaining lengths of strut to the cross braces, tying them together, using the fittings and 1/2 in hardware tightened to 50 ft/lbs
8. Install the snap pins through the uprights within 6 in of the bottom of the cross brace receiver
9. Install yellow caps on the tops of the upright

Quantity:

Contractor:

Project:

